SPECIFICATIONS		RZR Trail Sport	RZR Trail Ultimate	RZR Trail S Sport	RZR XP Sport	RZR XP 4 Sport
ENGINE & DRIVETRAIN	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
	Cylinders Displacement	875 cc	875 cc	875 cc	999 cc	999 cc
	Drive System Type	True on-demand AWD/2WD	High-performance true on-demand AWD/2WD/VersaTrac Turf Mode	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD
	Driveline Features	Yes	Yes	Not Equipped	Not equipped	Not equipped
	Engine Type	4-stroke DOHC twin cylinder	4-stroke DOHC twin cylinder	4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder
	Fuel System/Battery	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection
	Horsepower	75	75	100	114	114
	Transmission/Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H with geared reverse
DIMENSIONS	Bed Box Dimensions (L x W x H)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	20.7 x 37 x 7.9" (52.5 x 94 x 20 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)
	Box Capacity	300 lbs. (136.1 kg)	300 lbs. (136.1 kg)	300 lbs. (136.1 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)
	Curb Weight	1357 lbs. (616 kg)	1395 lbs. (633 kg)	1411 lbs (640kg)	1,674 lbs (760 kg) CA 1681 (762 kg)	1,960 lbs. (889kg) CA 1967 lbs. (801 kg)
	Estimated Dry Weight	1255 lbs (569 kg)	1314 lbs (596 kg)	1330lbs (603kg)	1,586 lbs (720 kg) CA 1593 (723 kg)	1,828lbs (829 kg) CA 1835 (832 kg)
	Fuel Capacity	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal (35.9 L)	9.5 gal. (36 L)	9.5 gal. (36 L)
	Ground Clearance	11" (27.9 cm)	11" (27.9 cm)	12.5" (31.8 cm)	14" (35.6 cm)	14" (35.6 cm)
	Towing Capacity	1,500 lbs. (680.4 kg)	1,500 lbs. (680.4 kg)	1,500 lbs. (680.4 kg)	N/A	N/A
	Hitch Type	Standard 1.25" (3.2 cm) receiver	Standard 1.25" (3.2 cm) receiver	Standard 1.25" (3.2 cm) receiver	N/A	N/A
	Overall Vehicle Size (L x W x H)	110.9 x 50 x 67.9" (282 x 127 x 172.5 cm)	110.9 x 50 x 67.9" (282 x 127 x 172.5 cm)	110.9 x 60 x 69.3" (282 x 152.4 x 176 cm)	119.5 x 64 x71.1" (303.5 x 162.6 x 180.6 cm)	146.9 x 64 x 72.8" (373.1 x 162.6 x 184.9 cm)
	Payload Capacity	740 lbs. (335.7 kg)	740 lbs. (335.7 kg)	740 lbs. (335.7 kg)	740 lbs. (336 kg)	900 lbs. (408 kg)
	Person Capacity	2	2	2	2	4
	Turning Radius	16'	13' 7"	16'	16.2'	20.1'
	Wheelbase	79" (200.7 cm)	79" (200.7 cm)	79" (200.7 cm)	90" (228.6 cm)	117" (297.2 cm)
SUSPENSION	Electronic Suspension Control System	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Front Shocks	ZF twin tube	FOX® 2.0 PODIUM X	ZF twin tube	2" Walker Evans® needle shocks with 16-position adjustable clickers	2" Walker Evans® needle shocks with 16-position adjustable clickers
	Front Suspension	Dual A-arm with stabilizer bar and 10" (25.4 cm) wheel travel	Dual A-arm with stabilizer bar and 10" (25.4 cm) wheel travel	Dual A-Arm with Stabilizer Bar and 12.25 in (31.1 cm) wheel travel	Dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel*, 16" (40.6 cm) of wheel travel	Dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel*, 16" (40.6 cm) of wheel travel
	Rear Shocks	ZF twin tube	FOX® 2.0 PODIUM X	ZF twin tube	2.5" Walker Evans® needle shocks with 16-position adjustable clickers	2.5" Walker Evans® needle shocks with 16-position adjustable clickers
	Rear Suspension	Dual A-arm with stabilizer bar and 10" (25.4 cm) wheel travel	Dual A-arm with stabilizer bar and 10" (25.4 cm) wheel travel	Dual A-Arm with Stabilizer Bar and 13.2 in (33.5 cm) wheel Travel	Trailing arm with stabilizer bar and 20" (50.8 cm) usable travel*, 18" (45.7 cm) of wheel travel	Trailing arm with stabilizer bar and 20" (50.8 cm) usable travel*, 18" (45.7 cm) of wheel travel
TIRES / WHEELS	Front Tires	26 X 8 X 12	26 X 8 X 12	27 x 9-12	29 x 9-14 radial tire	29 x 9-14 radial tire
	Rear Tires	26 X 9 X 12	26 X 9 X 12	27 x 11-12	29 x 11-14 radial Tire	30 x 10-14 radial tire
	Tire Ply Rating	3-Ply	3-Ply	6-Ply	8-ply	8-ply
	Wheels	Stamped steel	Cast aluminum	Cast aluminum	14" cast aluminum	14" cast aluminum
BRAKES	Front/Rear Brakes	4-wheel hydraulic disc with dual-bore front and rear calipers	4-wheel hydraulic disc with dual-bore front and rear calipers	4-wheel hydraulic disc with dual-bore front and rear calipers	4-wheel hydraulic disc with dual-bore front and single-bore rear calipers	4-wheel hydraulic disc with dual-bore front and single-bore rear calipers
	Parking Brake	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission
TECHNOLOGY	Audio System	Not equipped, accessory options available	Rockford Fosgate® Stage 2 audio	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available
	Connected Vehicle Services	Not equipped	Not equipped	Not equipped	Not equipped, accessory options available	Not equipped, accessory options available
	Touch Screen Display	Not equipped	7" Display powered by RIDE COMMAND, featuring built-in GPS navigation with topographic mapping, Group Ride (cell-based or GPS-based) with messaging, ride tracking, configurable gauges, waypoints, help alerts, AM/FM & weather radio, Bluetooth® audio & USB smartphone connectivity, and in-vehicle communications capability with optional Bluetooth® headsets.	Not equipped	Not equipped, accessory options available	Not equipped, accessory options available
	Camera	Not equipped	Rear camera	Not equipped	Not equipped, accessory options available	Not equipped, accessory options available
	Security	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system
COMFORT & CONVENIENCE	Driver Instrumentation	Dual-sweep analog dials with 4" LCD rider information center: user-selectable blue/red backlighting & brightness, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet + 12V power plug	Dual-sweep analog dials with 4" LCD rider information center: user-selectable blue/red backlighting & brightness, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet + 12V power plug	Dual-sweep analog dials with 4" LCD rider information center: user-selectable blue/red backlighting & brightness, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet + 12V power plug	Center mounted information center w/ 4" color display + rotary speedometer & tachometers, programmable speed limiting, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet	Center mounted information center w/ 4" color display + rotary speedometer & tachometers, programmable speed limiting, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet
	Seat Type	Bolstered bucket seats with standard driver and passenger seat sliders (tool required for adjustment on driver and passenger seat)	Bolstered bucket seats with standard driver and passenger seat sliders (tool required for adjustment on driver and passenger seat)	Bolstered bucket seats with standard driver and passenger seat sliders (tool required for adjustment on driver and passenger seat)	Bolstered bucket seats with driver seat slider, retractable 3-point seat belts	Bolstered bucket seats with driver & passenger seat slider, retractable 3-point seat belts, 2nd-row stadium-raised seating
	Steering	Adjustable tilt steering	Adjustable tilt steering	Adjustable tilt steering	Standard tilt	Standard tilt
	Electronic Power Steering	Equipped	Equipped	Equipped	Standard with quick turn rack	Standard with quick turn rack
	Drive Modes	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Cab Components	Half doors	Half doors, Roof	Half doors, Roof	Half doors	Half doors
	Heat and/or Air Conditioning	Not equipped	Not equipped	Not equipped	Not equipped	Not Equipped
	Speed Limiting	Not equipped	Not equipped	Not equipped	Programmable speed limiting	Programmable speed limiting
	Ride Control	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
LIGHTING & ELECTRICAL	Lighting	Signature white LED low/high Red LED tail/brake lights	Signature RZR Fang Accent Lighting, signature white LED low/high Red LED tail/brake lights	Signature white LED low/high Red LED tail/brake lights	LED headlights & taillights, illuminated in-cab controls	LED headlights & taillights, illuminated in-cab controls
	Electrical System	560-W Charging System @ 6000 RPM, 3-Position Pulse Bar	560-W Charging System @ 6000 RPM, 3-Position Pulse Bar	560-W Charging System @ 6000 RPM, 3-Position Pulse Bar	660-W Charging System @ 3,000 RPM, 6-Position PULSE Bar	660-W Charging System @ 3,000 RPM, 6-Position PULSE Bar
EXTERIOR FEATURES	Winch	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Vehicle Protection	Not equipped	Not equipped	Not equipped	Front bumper	Front bumper
	Door Type	Half doors	Half doors	Half doors	Half doors	Half doors
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
WARRANTY		Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty
DISCLAIMER		*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.

SPECIFICATIONS		RZR XP Ultimate	RZR XP 4 Ultimate	RZR XP S Sport	RZR XP S 4 Sport	RZR XP S Ultimate
ENGINE & DRIVETRAIN	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
	Cylinders Displacement	999 cc	999 cc	999 cc	999 cc	999 cc
	Drive System Type	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD	High-performance true on-demand AWD/2WD
	Driveline Features	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Engine Type	ProStar 1000 4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder	ProStar 1000 4-stroke DOHC twin cylinder
	Fuel System/Battery	Electronic fuel injection	Electronic fuel injection	Electronic Fuel Injection	Electronic fuel injection	Electronic fuel injection
	Horsepower	114	114	114	114	114
	Transmission/Final Drive	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H with geared reverse
DIMENSIONS	Bed Box Dimensions (L x W x H)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)	28 x 22 x 7" (72.0 x 57.0 x 17.8 cm)
	Box Capacity	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)
	Curb Weight	1,753 lbs. (795kg) CA 1760 lbs. (798 kg)	2,007 lbs. (910kg) CA 2014 lbs. (913 kg)	1,816 lbs. (824kg) CA 1823 lbs. (827 kg)	2,085 lbs. (946kg) CA 2092 lbs. (949 kg)	1,893 lbs. (859kg) CA 1900lbs. (862 kg)
	Estimated Dry Weight	1,665lbs (755 kg) CA 1672 (758 kg)	1,919lbs (870 kg) CA 1926 (873 kg)	1,726lbs (783 kg) CA 1733 (786 kg)	1,995lbs (905 kg) CA 2002 (908 kg)	1,803 lbs. (818kg) CA 1810 lbs. (821 kg)
	Fuel Capacity	9.5 gal. (36 L)	9.5 gal. (36 L)	9.5 gal. (36 L)	9.5 gal. (36 L)	9.5 gal. (36 L)
	Ground Clearance	14.5" (36.8 cm)	14.5" (36.8 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)
	Towing Capacity	N/A	N/A	N/A	N/A	N/A
	Hitch Type	N/A	N/A	N/A	N/A	N/A
	Overall Vehicle Size (L x W x H)	120 x 64 x 74" (304.8 x 162.6 x 188 cm)	147.8 x 64 x 75" (375.4 x 162.6 x 190.5 cm)	122 x 72 x 75.5" (309.9 x 182.9 x 191.8 cm)	149.8 x 72 x 76.5" (380.5 x 182.9 x 194.3 cm)	122 x 72 x 75.5" (309.9 x 182.9 x 191.8 cm)
	Payload Capacity	740 lbs. (336 kg)	900 lbs. (408 kg)	740 lbs. (336 kg)	900 lbs. (408 kg)	740 lbs. (336 kg)
	Person Capacity	2	4	2	4	2
	Turning Radius	16.2'	20.1'	20.1'	24.5'	20.1'
	Wheelbase	90" (228.6 cm)	117" (297.2 cm)	90" (228.6 cm)	117" (297.2 cm)	90" (228.6 cm)
SUSPENSION	Electronic Suspension Control System	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Front Shocks	2" Walker Evans® needle shocks with 16-position adjustable clickers	2" Walker Evans® needle shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers
	Front Suspension	Dual A-arm with stabilizer bar and 20.5" (52.07 cm) usable travel*, 16" (40.6 cm) of wheel travel	Dual A-arm with stabilizer bar and 20.5" (52.07 cm) usable travel*, 16" (40.6 cm) of wheel travel	Dual A-arm with stabilizer bar and 25" (63.5 cm) usable travel*, 19" (48.3 cm) of wheel travel	Dual A-arm with stabilizer bar and 25" (63.5 cm) usable travel*, 19" (48.3 cm) of wheel travel	Dual A-arm with stabilizer bar and 25" (63.5 cm) usable travel*, 19" (48.3 cm) of wheel travel
	Rear Shocks	2.5" Walker Evans® needle shocks with 16-position adjustable clickers	2.5" Walker Evans® needle shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers
	Rear Suspension	Trailing arm with stabilizer bar and 20.5" (52.07 cm) usable travel*, 18" (45.7 cm) of wheel travel	Trailing arm with stabilizer bar and 20.5" (52.07 cm) usable travel*, 18" (45.7 cm) of wheel travel	Trailing arm with stabilizer bar and 25" (63.5 cm) usable travel*, 21" (53.3 cm) of wheel travel	Trailing arm with stabilizer bar and 25" (63.5 cm) usable travel*, 21" (53.3 cm) of wheel travel	Trailing arm with stabilizer bar and 25" (63.5 cm) usable travel*, 21" (53.3 cm) of wheel travel
TIRES / WHEELS	Front Tires	30 x 10-14 radial tire	30 x 10-14 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire
	Rear Tires	30 x 10-14 radial tire	30 x 10-14 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	Pro Armor Trekker; 2.0 32 x 10-15 radial tire
	Tire Ply Rating	8-ply	8-ply	8-ply	8-ply	8-ply
	Wheels	14" cast aluminum	14" cast aluminum	15" cast-aluminum rim with 5-lug pattern	15" cast-aluminum rim with 5-lug pattern	15" cast-aluminum rim with 5-lug pattern
BRAKES	Front/Rear Brakes	4-wheel hydraulic disc with dual-bore front and single-bore rear calipers	4-wheel hydraulic disc with dual-bore front and dual-bore rear calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
	Parking Brake	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission
TECHNOLOGY	Audio System	Rockford Fosgate® Stage 3 audio (including 2 front & 2 rear co-axial speakers and external 400-W amp)	Rockford Fosgate® Stage 3 audio (including 2 front & 2 rear co-axial speakers and external 400-W amp)	Not equipped, accessory options available	Not equipped, accessory options available	Rockford Fosgate® Stage 3 audio (including 2 front & 2 rear co-axial speakers and external 400-W amp)
	Connected Vehicle Services	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available
	Touch Screen Display	7" Display powered by RIDE COMMAND, featuring built-in GPS navigation with topographic mapping, Group Ride (cell-based or GPS-based) with messaging, ride tracking, configurable gauges, waypoints, help alerts, AM/FM & weather radio, Bluetooth® audio & USB smartphone connectivity, and in-vehicle communications capability with optional Bluetooth® headsets.	7" Display powered by RIDE COMMAND, featuring built-in GPS navigation with topographic mapping, Group Ride (cell-based or GPS-based) with messaging, ride tracking, configurable gauges, waypoints, help alerts, AM/FM & weather radio, Bluetooth® audio & USB smartphone connectivity, and in-vehicle communications capability with optional Bluetooth® headsets.	Not equipped, accessory options available	Not equipped, accessory options available	7" Display powered by RIDE COMMAND, featuring built-in GPS navigation with topographic mapping, Group Ride (cell-based or GPS-based) with messaging, ride tracking, configurable gauges, waypoints, help alerts, AM/FM & weather radio, Bluetooth® audio & USB smartphone connectivity, and in-vehicle communications capability with optional Bluetooth® headsets.
	Camera	Equipped	Equipped	Not equipped, accessory options available	Not equipped, accessory options available	Equipped
	Security	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system
COMFORT & CONVENIENCE	Driver Instrumentation	Displayed on center 7" display Programmable speed limiting	Displayed on center 7" display Programmable speed limiting	Center mounted information center w/ 4" color display + rotary speedometer & tachometers, programmable speed limiting, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet	Center mounted information center w/ 4" color display + rotary speedometer & tachometers, programmable speed limiting, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet	Displayed on center 7" display Programmable speed limiting
	Seat Type	Bolstered bucket seats with driver seat slider, retractable 3-point seat belts	Bolstered bucket seats with driver & passenger seat slider, retractable 3-point seat belts, 2nd-row stadium-raised seating	Bolstered bucket seats with driver seat slider, retractable 3-point seat belts	Bolstered bucket seats with driver & passenger seat slider, retractable 3-point seat belts, 2nd-row stadium-raised seating	Bolstered bucket seats with driver seat slider, retractable 3-point seat belts
	Steering	Standard tilt	Standard tilt	Standard tilt	Standard tilt	Standard tilt
	Electronic Power Steering	Standard with quick turn rack	Standard with quick turn rack	Standard with quick turn rack	Standard with quick turn rack	Standard with quick turn rack
	Drive Modes	Not equipped	Not equipped	Rock, Standard, Sport	Rock, Standard, Sport	Rock, Standard, Sport
	Cab Components	Half doors, Poly roof	Half doors, Poly roof	Half doors	Half doors	Half doors, Poly roof
	Heat and/or Air Conditioning	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Speed Limiting	Programmable speed limiting	Programmable speed limiting	Programmable speed limiting	Programmable speed limiting	Programmable speed limiting
	Ride Control	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
LIGHTING & ELECTRICAL	Lighting	Signature RZR Fang Accent Lighting, LED headlights & taillights, illuminated in-cab controls	Signature RZR Fang Accent Lighting, LED headlights & taillights, illuminated in-cab controls	LED headlights & taillights, illuminated in-cab controls	LED headlights & taillights, illuminated in-cab controls	Signature RZR Fang Accent Lighting, LED headlights & taillights, illuminated in-cab controls
	Electrical System	900-W Charging System @ 3,000 RPM, 6-Position PULSE Bar	900-W Charging System @ 3,000 RPM, 6-Position PULSE Bar	660-W charging system @ 3,000 RPM, 6-position PULSE bar	660-W charging system @ 3,000 RPM, 6-position PULSE bar	900-W Charging System @ 3,000 RPM, 6-Position PULSE Bar
EXTERIOR FEATURES	Winch	Integrated 4,500-lb. winch	Integrated 4,500-lb. winch	Not equipped	Not equipped	Integrated 4,500-lb. winch
	Vehicle Protection	Front bumper	Front bumper	Front bumper	Front bumper	Front bumper
	Door Type	Half doors	Half doors	Half doors	Half doors	Half doors
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
WARRANTY		Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty
DISCLAIMER		*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available in North America	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available in North America	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available in North America

SPECIFICATIONS		RZR XP S 4 Ultimate	RZR Pro XP Sport	RZR Pro XP 4 Sport	RZR Pro XP Ultimate	RZR Pro XP 4 Ultimate
ENGINE & DRIVETRAIN	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
	Cylinders Displacement	999 cc	925 cc	925 cc	925 cc	925 cc
	Drive System Type	High-performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD
	Driveline Features	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Engine Type	ProStar 1000 4-stroke DOHC twin cylinder	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged
	Fuel System/Battery	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection
	Horsepower	114	181	181	181	181
	Transmission/Final Drive	Automatic PVT P/R/N/L/H with geared reverse	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
DIMENSIONS	Bed Box Dimensions (L x W x H)	28 x 22 x 7 in (72.0 x 57.0 x 17.8 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)
	Box Capacity	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)
	Curb Weight	2,112 lbs. (958kg) CA 2119 lbs. (961 kg)	1941 lbs. (880 kg)	2209 lbs. (1002 kg)	2,021 lbs. (917 kg)	2,329 lbs. (1056 kg)
	Estimated Dry Weight	2,022lbs (917 kg) CA 2029 (920 kg)	1,833 lbs. (831 kg)	2,102 lbs. (953 kg)	1,913 lbs. (868 kg)	2,218 lbs. (1006 kg)
	Fuel Capacity	9.5 gal. (36 L)	14.7 gal. (55.64 L)	17.4 gal. (65.86 L)	14.7 gal. (55.64 L)	17.4 gal. (65.86 L)
	Ground Clearance	16" (40.6 cm)	14.5" (36.8 cm)	14.5" (36.8 cm)	14.5" (36.8 cm)	14.5" (36.8 cm)
	Towing Capacity	N/A	N/A	N/A	N/A	N/A
	Hitch Type	N/A	Not equipped	Not equipped	Not equipped	Not equipped
	Overall Vehicle Size (L x W x H)	149.8 x 72 x 76.5"	126 x 64 x 71.7" (320 x 162.6 x 182.1 cm)	155 x 64 x 73.6" (393.7 x 162.6 x 186.9 cm)	126.1 x 64 x 71.7" (320 x 163 x 182 cm)	155 x 64 x 73.6" (393.7 x 162.6 x 186.9 cm)
	Payload Capacity	900 lbs. (408 kg)	740 lbs. (336 kg)	900 lbs. (408.2 kg)	740 lbs. (336 kg)	900 lbs. (408.2 kg)
	Person Capacity	4	2	4	2	4
	Turning Radius	24.5'	18.4'	21.7'	18.4'	21.7'
	Wheelbase	117" (297.2 cm)	96" (244 cm)	125" (317.5 cm)	96" (244 cm)	125" (317.5 cm)
SUSPENSION	Electronic Suspension Control System	Not equipped	Not equipped	Not equipped	Polaris DYNAMIX - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression damping on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Sport, Firm	Polaris DYNAMIX - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression damping on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Sport, Firm
	Front Shocks	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2" FOX shocks with position-sensitive spiral technology and QS3 compression adjusters	2" FOX shocks with position-sensitive spiral technology and QS3 compression adjusters	FOX 2.5 Podium Live Valve with bottom-out control (electronically controlled damping)	FOX 2.5 Podium Live Valve with bottom-out control (electronically controlled damping)
	Front Suspension	Dual A-arm with stabilizer bar and 25" (63.5 cm) usable travel*, 19" (48.3 cm) of wheel travel	High-clearance dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel, 17" (43.2 cm) wheel travel*	High-clearance dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel, 17" (43.2 cm) wheel travel*	High-clearance dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel, 17" (43.2 cm) wheel travel*	High-clearance dual A-arm with stabilizer bar and 20" (50.8 cm) usable travel, 17" (43.2 cm) wheel travel*
	Rear Shocks	2.5" Walker Evans® velocity shocks with 16-position adjustable clickers	2.5" FOX shocks with position-sensitive spiral technology and QS3 compression adjusters	2.5" FOX shocks with position-sensitive spiral technology and QS3 compression adjusters	FOX 2.5 Podium Live Valve with bottom-out control (electronically controlled damping)	FOX 2.5 Podium Live Valve with bottom-out control (electronically controlled damping)
	Rear Suspension	Trailing arm with stabilizer bar and 25" (63.5 cm) usable travel*, 21" (53.3 cm) of wheel travel	Trailing arm and standard-clearance radius rods with stabilizer bar and 22" (55.9 cm) usable travel, 20" (50.8 cm) wheel travel*	Trailing arm and standard-clearance radius rods with stabilizer bar and 22" (55.9 cm) usable travel, 20" (50.8 cm) wheel travel*	Trailing arm and high-clearance radius rods with stabilizer bar and 22" (55.9 cm) usable travel, 20" (50.8 cm) wheel travel*	Trailing arm and high-clearance radius rods with stabilizer bar and 22" (55.9 cm) usable travel, 20" (50.8 cm) wheel travel*
TIRES / WHEELS	Front Tires	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	30 x 10-14; wheel size 14 x 6	30 x 10-14; wheel size 14 x 6	30 x 10-14; wheel size 14 x 6	30 x 10-14; wheel size 14 x 6
	Rear Tires	Pro Armor Trekker; 2.0 32 x 10-15 radial tire	30 x 10-14; wheel size 14 x 7	30 x 10-14; wheel size 14 x 7	30 x 10-14; wheel size 14 x 7	30 x 10-14; wheel size 14 x 7
	Tire Ply Rating	8-ply	8-ply	8-ply	8-ply	8-ply
	Wheels	15" cast-aluminum rim with 5-lug pattern	14" cast aluminum rim with 4-lug pattern	14" cast aluminum rim with 4-lug pattern	14" cast aluminum rim with 4-lug pattern	14" cast aluminum rim with 4-lug pattern
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers	4-wheel hydraulic disc with dual-bore XL front and dual-bore rear calipers
	Parking Brake	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission
TECHNOLOGY	Audio System	Rockford Fosgate® Stage 3 audio (including 2 front & 2 rear co-axial speakers and external 400-W amp)	Not equipped, accessory options available	Not equipped, accessory options available	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.
	Connected Vehicle Services	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available
	Touch Screen Display	7" Display powered by RIDE COMMAND, featuring built-in GPS navigation with topographic mapping, Group Ride (cell-based or GPS-based) with messaging, ride tracking, configurable gauges, waypoints, help alerts, AM/FM & weather radio, Bluetooth® audio & USB smartphone connectivity, and in-vehicle communications capability with optional Bluetooth® headsets.	Not equipped, accessory options available	Not equipped, accessory options available	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update
	Camera	Equipped	Not equipped, accessory options available	Not equipped, accessory options available	Digital Rear Camera	Digital Rear Camera
	Security	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system
COMFORT & CONVENIENCE	Driver Instrumentation	Displayed on center 7" display Programmable speed limiting	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system
	Seat Type	Bolstered bucket seats with driver & passenger seat slider, retractable 3-point seat belts, 2nd-row stadium-raised seating	Bolstered bucket seats with driver 4-way adjustability (including 6" front-to-back toolless seat slider and tilt adjustable capability) and passenger tilt adjustability; 3-pt. height-adjustable seatbelts	Bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); 3-pt. height-adjustable seatbelts; rear stadium-style seating with 3-pt. height-adjustable seatbelts.	Bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability) and passenger tilt adjustability; Sub-Zero 4-point harness.	Bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); Sub-Zero 4-point harness; rear stadium-style seating with Sub-Zero 4-point harness.
	Steering	Standard tilt	Race-inspired steering wheel with tilt adjustment	Race-inspired steering wheel with tilt adjustment	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.
	Electronic Power Steering	Standard with quick turn rack	High Assist Electronic Power Steering with Quick Turn Rack	High-assist electronic power steering with quick-turn rack	High-assist electronic power steering with quick-turn rack	High-assist electronic power steering with quick-turn rack
	Drive Modes	Rock, Standard, Sport	Not equipped	Not equipped	Not equipped	Not equipped
	Cab Components	Half doors, Poly roof	Half doors, poly roof	Half doors, poly roof	Half doors, poly roof	Half doors, poly roof
	Heat and/or Air Conditioning	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Speed Limiting	Programmable speed limiting	Not equipped	Not equipped	Not equipped	Not Equipped
	Ride Control	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
LIGHTING & ELECTRICAL	Lighting	Signature RZR Fang Accent Lighting, LED headlights & taillights, illuminated in-cab controls	White LED low/high and red LED tail/brake lights.	White LED low/high and red LED tail/brake lights.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.
	Electrical System	900-W Charging System @ 3,000 RPM, 6-Position PULSE Bar	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM
EXTERIOR FEATURES	Winch	Integrated 4,500-lb. winch	Not equipped	Not equipped	Not equipped	Not equipped
	Vehicle Protection	Front bumper	Bull Bumper	Bull Bumper	Bull bumper	Bull bumper
	Door Type	Half doors	Half doors	Half doors	Half doors	Half doors
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride; convertible fold-flat rear seat storage with integrated tie-down points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)
WARRANTY		Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty
DISCLAIMER		*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available in North America	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.

SPECIFICATIONS		RZR Pro S Sport	RZR Pro S 4 Sport	RZR Pro S Ultimate	RZR Pro S 4 Ultimate	RZR Pro R Ultimate
ENGINE & DRIVETRAIN	Cooling	Liquid	Liquid	Liquid	Liquid	Liquid
	Cylinders Displacement	925 cc	925 cc	925 cc	925 cc	1997 cc
	Drive System Type	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Isolated Xtreme Performance true on-demand AWD/2WD	Race Performance true 2WD/4WD/4WD Lock
	Driveline Features	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Engine Type	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC twin-cylinder turbocharged	4-stroke DOHC inline four-cylinder
	Fuel System/Battery	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection
	Horsepower	181	181	181	181	225
	Transmission/Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
DIMENSIONS	Bed Box Dimensions (L x W x H)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	26 x 17.7 x 11.5" (66 x 45 x 29.2 cm)	29.5 x 23.8 x 8.1" (75 x 60.5 x 20.6 cm)
	Box Capacity	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)	300 lbs. (136 kg)
	Curb Weight	2,123 lbs. (963 kg)	2,403 lbs. (1090 kg)	2,201 lbs. (998 kg)	2,502 lbs. (1134 kg)	2452 lbs. (1112 kg)
	Estimated Dry Weight	2,013 lbs. (913 kg)	2,287 lbs. (1037 kg)	2,091 (948 kg)	2,386 lbs. (1082 kg)	2,339 lbs. (1061 kg)
	Fuel Capacity	14.7 gal (55.64 L)	17.4 gal. (65.86 L)	14.7 gal. (55.64 L)	17.4 gal. (65.86 L)	14.7 gal. (55.64 L)
	Ground Clearance	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)
	Towing Capacity	N/A	N/A	N/A	N/A	N/A
	Hitch Type	Not equipped	Not Equipped	Not equipped	Not equipped	Not equipped
	Overall Vehicle Size (L x W x H)	128 x 74 x 74.4" (325 x 188 x 189 cm)	157 x 74 x 77" (340 x 188 x 196 cm)	128 x 74 x 74.43" (25 x 188 x 189 cm)	157 x 74 x 77" (340 x 188 x 196 cm)	136.5 x 74 x 72.8" (347 x 188 x 185 cm)
	Payload Capacity	730 lbs. (331 kg)	1,160 lbs. (526 kg)	730 lbs. (331 kg)	1,160 lbs. (526 kg)	740 lbs. (335.6 kg)
	Person Capacity	2	4	2	4	2
	Turning Radius	19.5'	23.5'	19.5'	23.5'	20.1'
	Wheelbase	96" (244 cm)	125" (317.5 cm)	96" (244 cm)	125" (317.5 cm)	104.5" (265.4cm)
SUSPENSION	Electronic Suspension Control System	Not equipped	Not equipped	Polaris DYNAMIX - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression damping on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Sport, Firm	Polaris DYNAMIX - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression damping on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Sport, Firm	Polaris DYNAMIX DV (Dual Valve) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja
	Front Shocks	Walker Evans® 2.5" velocity needle shock with 16-position adjustable clickers	Walker Evans® 2.5" velocity needle shock with 16-position adjustable clickers	FOX 3.0 Live Valve internal bypass with bottom-out control (electronically controlled damping)	FOX 3.0 Live Valve internal bypass with bottom-out control (electronically controlled damping)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)
	Front Suspension	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs
	Rear Shocks	Walker Evans® 3" velocity needle shock with 16-position adjustable clickers	Walker Evans® 3" velocity needle shock with 16-position adjustable clickers	FOX 3.0 Live Valve internal bypass with bottom-out control (electronically controlled damping)	FOX 3.0 Live Valve internal bypass with bottom-out control (electronically controlled damping)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)
	Rear Suspension	Tubular trailing arm with boxed gusseting and toe link, stabilizer bar, 28.3" (71.9 cm) usable travel, 22.4" (56.9 cm) wheel travel, unitized hubs	Tubular trailing arm with boxed gusseting and toe link, stabilizer bar, 28.3" (71.9 cm) usable travel, 22.4" (56.9 cm) wheel travel, unitized hubs	Tubular trailing arm with boxed gusseting and toe link, high-clearance radius rods, stabilizer bar, 28.3" (71.9 cm) usable travel, 22.4" (56.9 cm) wheel travel, unitized hubs	Tubular trailing arm with boxed gusseting and toe link, high-clearance radius rods, stabilizer bar, 28.3" (71.9 cm) usable travel, 22.4" (56.9 cm) wheel travel, unitized hubs	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs
TIRES / WHEELS	Front Tires	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7
	Rear Tires	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7
	Tire Ply Rating	8-ply	8-ply	8-ply	8-ply	8-ply
	Wheels	15" cast aluminum rim with 5-lug pattern	15" cast aluminum rim with 5-lug pattern	15" cast aluminum rim with 5-lug pattern	15" cast aluminum rim with 5-lug pattern	5-lug, 15" cast aluminum rim with beadlock
BRAKES	Front/Rear Brakes	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor
	Parking Brake	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission
TECHNOLOGY	Audio System	Not equipped, accessory options available	Not equipped, accessory options available	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.
	Connected Vehicle Services	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	Not equipped, accessory options available	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.
	Touch Screen Display	Not equipped, accessory options available	Not equipped, accessory options available	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update
	Camera	Not equipped, accessory options available	Not equipped, accessory options available	Digital Rear Camera	Digital Rear Camera	Digital Rear Camera
	Security	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system
COMFORT & CONVENIENCE	Driver Instrumentation	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system
	Seat Type	Bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability) and passenger tilt adjustability; Sub-Zero 4-point harness.	Bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat sliderand tilt adjustability); Sub-Zero 4-point harness; rear stadium-style seating with Sub-Zero 4-point harness.	Bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability) and passenger tilt adjustability; Sub-Zero 4-point harness.	Bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat sliderand tilt adjustability); Sub-Zero 4-point harness; rear stadium-style seating with Sub-Zero 4-point harness.	Heated and vented, bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); passenger tilt adjustability; retractable 6-Point harnesses.
	Steering	Race-inspired steering wheel with tilt adjustment	Race-inspired steering wheel with tilt adjustment	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.
	Electronic Power Steering	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.
	Drive Modes	Not equipped	Not equipped	Not equipped	Not equipped	Rock, Sport, Race
	Cab Components	Half doors, poly roof	Half doors, poly roof	Half doors, poly roof	Half doors	Half doors, aluminum roof
	Heat and/or Air Conditioning	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Speed Limiting	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Ride Control	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
LIGHTING & ELECTRICAL	Lighting	White LED low/high and red LED tail/brake lights.	White LED low/high and red LED tail/brake lights.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.
	Electrical System	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM	High-output 900-W charging system @ 3,000 RPM	High-output 1,700-W charging system @ 3,000 RPM
EXTERIOR FEATURES	Winch	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Vehicle Protection	Bull Bumper	Bull Bumper	Bull bumper	Bull bumper	Bull bumper
	Door Type	Half doors	Half doors	Half doors	Half doors	Half doors
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride; convertible fold-flat rear seat storage with integrated tie-down points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)	Lock & Ride; Factory-equipped cargo liner
WARRANTY		Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty
DISCLAIMER		*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate.	*Usable Travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.

SPECIFICATIONS		RZR Pro R 4 Ultimate	RZR Pro R Boost Ultimate	RZR Pro R 4 Boost Ultimate	RZR Pro R Boost Ultra	RZR Pro R 4 Boost Ultra
ENGINE & DRIVETRAIN	Cooling	Liquid	Rear Mounted Radiator, Liquid	Rear Mounted Radiator, Liquid	Rear Mounted Radiator, Liquid	Rear Mounted Radiator, Liquid
	Cylinders Displacement	1997 cc	1997 cc	1997 cc	1997 cc	1997 cc
	Drive System Type	Race Performance true 2WD/4WD/4WD Lock	Race Performance true 2WD/4WD/4WD Lock	Race Performance true 2WD/4WD/4WD Lock	Race Performance true 2WD/4WD/4WD Lock	Race Performance true 2WD/4WD/4WD Lock
	Driveline Features	Not equipped	Transmission Cooler	Transmission Cooler	Transmission Cooler	Transmission Cooler
	Engine Type	4-stroke DOHC inline four-cylinder	4-stroke DOHC inline four-cylinder turbocharged	4-stroke DOHC inline four-cylinder turbocharged	4-stroke DOHC inline four-cylinder turbocharged	4-stroke DOHC inline four-cylinder turbocharged
	Fuel System/Battery	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection	Electronic fuel injection
	Horsepower	225	275	275	275	275
	Transmission/Final Drive	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H	Automatic PVT P/R/N/L/H
DIMENSIONS	Bed Box Dimensions (L x W x H)	29.5 x 23.8 x 8.1" (75 x 60.5 x 20.6 cm)	24.3 x 12.3 x 10.6" (61.7 x 31.2 x 26.9 cm)	24.3 x 12.3 x 10.6" (61.7 x 31.2 x 26.9 cm)	24.3 x 12.3 x 10.6" (61.7 x 31.2 x 26.9 cm)	24.3 x 12.3 x 10.6" (61.7 x 31.2 x 26.9 cm)
	Box Capacity	300 lbs. (136 kg)	150 lbs. (68 kg)	150 lbs. (68 kg)	150 lbs. (68 kg)	150 lbs. (68 kg)
	Curb Weight	2769 (1256 kg)	2671 lbs. (1212 kg)	2906 lbs (1318 kg)	2693 lbs (1222 kg)	3011 lbs (1366 kg)
	Estimated Dry Weight	2,594 lbs. (1177 kg)	2531 lbs. (1148 kg)	2824 lbs (1281 kg)	2553 lbs (1158 kg)	2852 lbs (1294 kg)
	Fuel Capacity	17.4 gal. (65.86 L)	14.7 gal. (55.64 L)	17.4 gal. (65.86 L)	14.7 gal. (55.64 L)	17.4 gal. (65.86 L)
	Ground Clearance	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)	16" (40.6 cm)
	Towing Capacity	N/A	N/A	N/A	N/A	N/A
	Hitch Type	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Overall Vehicle Size (L x W x H)	165.5 x 74 x 76.5" (420 x 188 x 194 cm)	136.5 x 74 x 76.4" (347 x 188 x 194 cm)	165.5 x 74 x 80.1" (420 x 188 x 203 cm)	136.5 x 74 x 76.4" (347 x 188 x 194 cm)	165.5 x 74 x 80.1" (420 x 188 x 203 cm)
	Payload Capacity	900 lbs. (408 kg)	740 lbs. (335.6 kg)	1010 lbs (458 kg)	740 lbs. (335.6 kg)	1010 lbs (458 kg)
	Person Capacity	4	2	4	2	4
	Turning Radius	25.0'	20.1'	25.0'	20.1'	25.0'
	Wheelbase	133.5" (339.1cm)	104.5" (265.4cm)	133.5" (339.1cm)	104.5" (265.4cm)	133.5" (339.1cm)
SUSPENSION	Electronic Suspension Control System	Polaris DYNAMIX DV (Dual Valve) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja	Polaris DYNAMIX DV (Dual Valve) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja	Polaris DYNAMIX DV (Dual Valve) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja	Polaris DYNAMIX DVS (Dual Valve & Stabilizer Bar Links) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock and locks/unlocks each stabilizer bar link at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja	Polaris DYNAMIX DVS (Dual Valve & Stabilizer Bar Links) - Smart suspension system with onboard inertial measurement unit (IMU) and control module (SCM) actively controls compression & rebound damping independently on each shock and locks/unlocks each stabilizer bar link at up to 200 times/sec. Selectable ride modes: Comfort, Rock, Track, Baja
	Front Shocks	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)
	Front Suspension	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs	Stamped & welded boxed dual A-arms with 3-piece stabilizer bar and 27" (68.6 cm) usable travel, 22.25" (56.5 cm) wheel travel, unitized hubs
	Rear Shocks	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)	FOX 3.0 Live Valve X2 internal bypass (electronically controlled compression and rebound)
	Rear Suspension	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs	Boxed trailing arm with toe link, high-clearance radius rods, 3-piece stabilizer bar, 29.0" (73.7 cm) usable travel, 24.5" (62.2 cm) wheel travel, unitized hubs
TIRES / WHEELS	Front Tires	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32x10R15 BFGoodrich® Mud-Terrain T/A KM3	32x10R15 BFGoodrich® Mud-Terrain T/A KM3
	Rear Tires	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32 x 10-15 Pro Armor Trekker; wheel size 15 x 7	32x10R15 BFGoodrich® Mud-Terrain T/A KM3	32x10R15 BFGoodrich® Mud-Terrain T/A KM3
	Tire Ply Rating	8-ply	8-ply	8-ply	8-ply	8-ply
	Wheels	5-lug, 15" cast aluminum rim with beadlock	5-lug, 15" cast aluminum rim with beadlock	5-lug, 15" cast aluminum rim with beadlock	5-lug, 15" cast aluminum rim with beadlock	5-lug, 15" cast aluminum rim with beadlock
BRAKES	Front/Rear Brakes	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor	4-wheel hydraulic disc with triple-bore front and dual-bore rear calipers; aluminum top hat rotor
	Parking Brake	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission	Park in-transmission
TECHNOLOGY	Audio System	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.	Factory-integrated, Rockford Fosgate tuned Stage 4 audio system. Includes (1) 1500W 8-channel digital amplifier, (2) 100W 1" tweeters, (2) 100W 6.5" component front speakers, (2) 100W 6.5" coaxial rear speakers, and (1) 10" subwoofer. *Audio System is IPX7 and IPX9K water immersion tested to withstand the wet elements.
	Connected Vehicle Services	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.	RIDE COMMAND+ connected vehicle services including real time vehicle location, vehicle security alerts, remote ignition lockout, vehicle health diagnostics, and maintenance reminders. Free three-year subscription of RIDE COMMAND+ included with purchase of vehicle when factory installed.
	Touch Screen Display	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update	10.4" Touchscreen HD Display powered by RIDE COMMAND, featuring Apple CarPlay®*, split screen mapping with built in GPS (3D, topographic & satellite), Group Ride (cell based or vehicle-to-vehicle) with messaging, configurable gauges and controls, DYNAMIX suspension visualizer, digital audio interface with Bluetooth® audio & USB connectivity, AM/FM & weather radio, hard buttons with volume knob, and in vehicle communications capability with optional Bluetooth® headsets. *Apple CarPlay® functionality available in future software update
	Camera	Digital Rear Camera	Digital Rear Camera	Digital Rear Camera	Digital Rear Camera	Digital Rear Camera
	Security	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system	Polaris P.A.S.S anti-theft system
COMFORT & CONVENIENCE	Driver Instrumentation	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system	Driver Forward Information Center with 4" color display + rotary speedometer & tachometers, programmable service intervals, speedometer, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder light, gear indicator, DC outlet, Polaris P.A.S.S anti-theft system
	Seat Type	Front: Heated and vented, bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); retractable 6-Point harnesses. Rear: Stadium-style seating with 6-point harnesses.	Heated and vented, bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); passenger tilt adjustability; retractable 6-Point harnesses.	Front: Heated and vented, bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); retractable 6-Point harnesses. Rear: Stadium-style seating with 6-point harnesses.	Heated and vented, bolstered bucket seats with driver-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); passenger tilt adjustability; retractable 6-Point harnesses.	Front: Heated and vented, bolstered bucket seats with driver- and passenger-4-way adjustability (including 6" front-to-back tool-less seat slider and tilt adjustability); retractable 6-Point harnesses. Rear: Stadium-style seating with 6-point harnesses.
	Steering	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	Race-inspired steering wheel with tilt and telescoping adjustment; DYNAMIX and RIDE COMMAND push-button controls.	MPI GT racing steering wheel, tilt and telescoping adjustment; DYNAMIX and Ride Command push-button controls.	MPI GT racing steering wheel, tilt and telescoping adjustment; DYNAMIX and Ride Command push-button controls.
	Electronic Power Steering	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.	Rack-mounted high-assist electronic power steering with quick-turn rack.
	Drive Modes	Rock, Sport, Race	Rock, Sport, Race	Rock, Sport, Race	Rock, Sport, Race	Rock, Sport, Race
	Cab Components	Half doors, aluminum roof	Half doors, Color matched aluminum roof w/ air scoop	Half doors, Color matched aluminum roof w/ air scoop	Half doors, Color matched aluminum roof w/ air scoop	Half doors, Color matched aluminum roof w/ air scoop
	Heat and/or Air Conditioning	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Speed Limiting	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Ride Control	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
LIGHTING & ELECTRICAL	Lighting	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.	Signature animated RZR Fang Accent Lighting; white LED low/high and red LED tail/brake lights; animated interior accent lighting.
	Electrical System	High-output 1,700-W charging system @ 3,000 RPM	High-output 1,700-W charging system @ 3,000 RPM	High-output 1,700-W charging system @ 3,000 RPM	High-output 1,700-W charging system @ 3,000 RPM	High-output 1,700-W charging system @ 3,000 RPM
EXTERIOR FEATURES	Winch	Not equipped	Not equipped	Not equipped	Not equipped	Not equipped
	Vehicle Protection	Bull bumper	Bull bumper	Bull bumper	Bull bumper	Bull bumper
	Door Type	Half doors	Half doors	Half doors	Half doors	Half doors
	Cargo System	Lock & Ride; Factory-equipped cargo liner; Convertible fold-flat rear seat storage with integrated tie-down points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)	Lock & Ride; Factory-equipped cargo liner	Lock & Ride; Factory-equipped cargo liner; Convertible fold-flat rear seat storage with integrated tie-down points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)	Lock & Ride; Factory-equipped cargo liner	Lock & Ride; Factory-equipped cargo liner; Convertible fold-flat rear seat storage with integrated tie-down points, 27.7 x 52.8 x 19.5" (70.4 x 134.1 x 49.53 cm)
WARRANTY		Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty	Factory 1-Year Limited Warranty
DISCLAIMER		*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.	*Usable travel is measured, with the vehicle in full droop, from the bottom of the tire to the bottom of the skid plate. *Group Ride only available on North America models.